

ART MICROMIX

75,00 € tax included

Reference: ARMICROMIX

ART MICROMIX



ART MicroMIX - Microphone Preamp w/ Phantom Power

Simplicity and economy are important factors. A level control and a simple overload indicator such as a Clip LED will also help you to keep the signal clean.

Sometimes you need to connect a low-impedance or condenser microphone to something which does not support it, such as a high-impedance mixer input, a PC sound card, a powered speaker or possibly an instrument amp. Situations like this call for a mic preamp like the MicroMIX to act as an interface. Simplicity and economy are important factors. A level control and a simple overload indicator such as a Clip LED will also help you to keep the signal clean.

Specs

Maximum Gain 50dB (XLR), 44dB (1/4in)
Input Impedance 10K Ohms (balanced and unbalanced)
IMD (SMPTE) less than 0.01%
Maximum Input Level 0dBV balanced (XLR), +10dBV unbalanced (1/4in)
Input Connectors Bal./low-imped. XLR, Unbal. 1/4 in Line Input
Output Connectors Bal. XLR line, Unbalanced 1/4 in Line/Headphone
Power Requirements 12V DC (Adapter included)
EIN less than 0.01%
Phase Shift less than 10 degrees 20Hz – 20kHz
Phantom Power +36 volt, (for the XLR input)
Power and Clip LEDs
Dimensions 4.5x2.875x1.5 inch (150mm x 75mm x 38mm)
Weight 1.2 lbs. (544g)