

## KLARK TEKNIK DN-6000

**3.750,00 € tax included**

Reference: KTDN6000

## KLARK TEKNIK DN-6000



### TECHNICAL SPECIFICATION

Frequency Response 5Hz to 40kHz  
Microphone Input Differential .25mV/uBar to 1mV/uBar  
Sensitivity 140dBspl to 50dBspl  
Powering 48V dc phantom power (nominal)  
Connector XLR on front panel  
Line Input Two, Differential - balanced or unbalanced  
Sensitivity 40dBu to -50dBmin  
Impedance 47k ohm  
Connector XLRs on rear panel  
Attenuation accuracy +/-0.1dB  
'A'-weighting Selectable to IEC 651 type 1 requirement  
'C'-weighting Selectable to IEC 651 type 1 requirement  
Pink Noise output Digital pseudo-random white noise generator  
with pink noise filter  
Frequency distribution -3dB/Octave 20Hz to 20kHz +\_0.2dB  
Level +4dBu, -10dBu, -30dBu  
Impedance 50 ohms balanced  
Connector XLR on rear panel  
Interfaces DN3600, parallel printer, Open Architecture  
Port  
Power requirements  
Voltage 100 to 240, 50 to 60Hz  
Consumption Less than 40VA  
Weight  
Net  
Shipping Dimensions  
Width 482mm  
Depth  
Height 89mm  
Optional 6051 Microphone

Frequency Response Flat to 15KHz  
Sensitivity 0.5mV per uBar nominal @ 1kHz  
Dynamic range 20 to 130dBspl  
Capsule 0.25 inch electret condenser  
Type pressure - omni directional  
Power required 14V Phantom power