

CARVER PXM-250 FINALE STEREO 75W/8 - 125W/4 - 2U



399,00 € tax included

Reference: CAPXM250

CARVER PXM-250 FINALE STEREO 75W/8 - 125W/4
- 2U

250W bridged mono into 8 ohms

175W per channel into 2 ohms

125W per channel into 4 ohms

75W per channel into 8 ohms

• Three connector versions available:

Standard - XLR and 1/4" TRS inputs with

Multi-way Binding Posts

BR Version - Barrier Strip inputs with

Multi-way Binding Posts

SP Version - XLR and 1/4" TRS inputs with

Neutrik™ Speakons™

• Independent level controls for CH1 & CH2

• Independent CH1 and CH2 switchable High Pass

Filters, selectable at 30Hz or 80Hz

• Independent CH1 and CH2 selectable Clip Limiters

• Independent CH1 and CH2 selectable Input

Sensitivity @ 0.775Vrms or 1.5Vrms

• Externally configurable for Parallel Mono mode,

to operate both channels with a mono signal

• Externally configurable for Bridged Mono mode,

to combine the power of both channels into a

higher powered mono channel

• Protection circuitry includes Thermal and

Short Circuit

• Power Ready, Signal Present, Clip, Protect and

Thermal LED indicators for each channel

• Variable speed fan cooling

• RAMP optional computer monitoring port