

KME VL6I PASSIVE 2-WAY LOUDSPEAKER

376,00 € tax included

Reference: KMVL6IBK

KME VL6I PASSIVE 2-WAY LOUDSPEAKER



The new VL 6 i is a passive 2-way installation loudspeaker with extremely brilliant and clear sound quality. It is designed for music and speech reproduction as top unit, in combination with a VERSIO subwoofer or as fullrange speaker. Meeting and seminar rooms, churches and theatres, multimedia presentations, surround sound applications, clubs and discotheques, restaurants, near field sound distribution

Specifications:

Components: 6" + 1" Neodymium

Dispersion (h x v): 85° x 55° Waveguide elliptical

Nominal load AES/prog. (watts): 200 / 400

Impedance (Ohm): 8

SPL (nom./max.) dB: 93 / 116

Frequency range: 80 Hz - 19 kHz

Crossover frequency (Hz/24dB): 2.000

Connectors: 2 x terminal screw connectors, 2 x Speakon optional

Finish: PU coating black (white optional), weather resistant' impregnation of loudspeaker membrane

Special features: 10 M8 treads, Protection class IP 44

Protective grille: high protective comb grid with acoustic foam

Dimensions (W x H x D) mm: 235 x 405 x 190

Weight (kg): 7

Design: top unit / fullrange