

BOSE F1 SUBWOOFER ATTIVO 2x10" 1000W

1.199,00 € tax included

Reference: BOF1SUB



BOSE F1 SUBWOOFER 2X10"

***** PRODOTTO IN ESPOSIZIONE *****

***** PRODOTTO IN ESPOSIZIONE *****

System Performance:

System Type Self powered

Frequency Response (-3 dB) 40 Hz – 250 Hz

Frequency Range (-10 dB) 38 Hz – 250 Hz

Nominal Dispersion Omni-directional

Maximum SPL @ 1 m 130 dB SPL (peak 6 dB CF)

Crossover Frequency 40 – 100 Hz Butterworth Bandpass, 100 Hz 4th order Butterworth HPF at Line Out

Amplification:

System Power 1000 W

Distortion at Rated Power 0.1 % Max (30 Hz - 15 kHz)

System Limiter Dynamic limiter

Power Indicator Blue LED: system on

Transducers:

Driver Compliment 2 x 10" high-excursion drivers

Channels:

Channels 1/2

Signal Indicators POWER/FAULT, LIMIT, FRONT LED, SIGNAL INPUT

Input Connections 2 XLR - 1/4" Combo

Controls Volume level, Front LED function select, Power on/off, Polarity select, Line output EQ

Additional Connections:

Line Output XLR balanced

AC Mains IEC Connector

Physical:

Enclosure Wood cabinet with high impact composite end caps

Grille Powder-coated perforated steel grille
Dimensions 27" H x 16.1" W x 17.6" D (688 x 410.16 x 448.5mm)
Net Weight 55 lbs (24.9 kg)

Power Supply Voltages:
Universal AC power rating: 100-240 V 50 / 60 Hz +/- 20 %, 200 W max