

LD SYSTEMS STINGER SUB 15 A G3 SUBWOOFER ATTIVO 1x15" 450W

829,00 € tax included

Reference: LDESUB15AG3



LD SYSTEMS STINGER SUB 15 A G3 SUBWOOFER
ATTIVO 1X15" 450W

Active 15" bass-reflex PA subwoofer

- High-efficiency 450 watts RMS digital power stage and 133 dB max. SPL
- 15" custom design woofer for extended low end down to 40 Hz
- DynX® DSP technology for distortion-free performance
- 80, 100 and 120 Hz low pass presets
- Cardioid subwoofer array presets
- Horizontal or vertical placement
- 18 mm birch ply cabinet with ultra rugged polyurea finish
- Ergonomic handles and stacking recesses for easy transport and setup
- Shock-resistant front grill provides maximum speaker protection

Engineered for rock-solid reliability day in, day out this active subwoofer is a truly professional performer. With built-in presets for quick system integration and a variety of cardioid array configurations it is completely user-friendly. The Stinger® SUB 15 A G3 is powered by high efficiency Class D amplification with a mighty 450 watts RMS output. It drives a custom designed 15" woofer delivering a huge bottom end with terrific punch and excellent definition. The Stinger® SUB 15 A G3 incorporates LD Systems' proprietary DynX® DSP technology to ensure top-level performance and pristine, distortion-free bass reproduction at all times. Designed to be a real workhorse throughout, the well-braced bass reflex enclosure is constructed for horizontal and vertical orientation. It is made of rigid 18 mm birch ply and coated with ultra tough polyurea for extraordinary strength and durability. Sporting a steel front grille, M20 threaded pole insert, stacking recesses and ergonomic handles the Stinger® 15 A G3 is an attractively priced choice for truly professional sound reinforcement. A large selection of accessories facilitate live and installed applications.

- Tipo di prodotto: Subwoofer PA
- Tipo: Attivo
- Dimensioni: woofer 15 "
- Dimensioni: woofer 381 mm
- Magnete woofer: Ferrite
- Marca woofer: Custom Made
- Bobina woofer: 3 "
- Bobina woofer: 76,5 mm
- Amplifier Classe: D

- Potenza (RMS): 450 W
- Potenza (picco): 900 W
- Risposta in frequenza: 40 - 200 Hz
- SPL max: (picco) 133 dB
- Protezioni: Cortocircuito , DC , Limitatore , Sovracorrente
- Impedenza di ingresso: 30000 Ohm
- Sensibilità di ingresso: 0,3 V
- Elementi di comando: Livello Main , Mode
- Indicatori: Limit , Mode , On , Protect (protezione attiva) , Segnale
- Ingressi di linea: 2
- Connessioni di ingresso di linea: Jack da 6,3 mm , XLR
- Uscite di linea: 2
- Connessioni di uscita di linea: XLR
- Alimentazione: SMPS
- Power Consumption: (max.) 600 VA
- Temperatura di esercizio: 0 - 40 °C
- Umidità relativa: - Materiale cassa: Compensato 18 mm
- Superficie cassa: Poliurea
- Modello cassa: Bass reflex
- Larghezza: 567 mm
- Altezza: 477 mm
- Profondità: 624 mm
- Peso: 31,9 kg