

## FOCAL SM9L STUDIO MONITOR ATTIVO LEFT

**2.205,00 € tax included**

Reference: FOSM9L

FOCAL SM9L STUDIO MONITOR ATTIVO LEFT



### Specifiche Tecniche:

- Risposta in frequenza:
- 3 way mode : 30Hz - 40kHz (+/- 3dB) ' 40Hz - 20kHz (+/- 1dB)
- 2 way mode: 90Hz - 20kHz (+/- 3dB)
- Massimo SPL:
- 3 way mode: 116dB SPL (peak @ 1m) '
- 2 way mode: 106dB SPL (peak @ 1m)
- Input: Tipo / Impedenza: Bilanciato Elettronicamente/ 10 kOhms
- Connettori: XLR
- Sensibilità: Selezionabile, +4dBu o -10dBV
- Basso: 400W, class AB
- Medie: 100W, class AB
- Alte: 100 W, classe AB
- Alimentazione:
- Locale: 230V (fusibile 3,15A) - 115V (6,3A)
- Connessioni: presa IEC e cavo di potenza
- Indicatori:
- Rear Panel
- Input sensitivity selector (+4dBu / -10dBV)
- High-pass crossover (full range, 45, 60, 90Hz @ -6dB)
- Low frequency shelving
- (+/- 3dB from 30 to 250Hz per step of 0.5dB)
- High frequency shelving
- (+/- 3dB from 4.5 to 40kHz per step of 0.5dB)
- Low frequency EQ
- (+/- 3dB per step of 0.5dB @ 50Hz, Q factor = 2)
- Low-mid frequency EQ
- (+/- 3dB per step of 0.5dB @ 160Hz, Q factor = 1)
- Mid frequency EQ
- (+/- 3dB per step of 0.5dB @ 1kHz, Q factor = 0.6)
- Side panel
- Stand By / On switch
- Direct switch

- Focus switch
- Spia luminosa: Power On, clipping and default on front panel LED
- Radiatore passivo: 11WPP52, 11" (27cm) Focal "W" composite sandwich cone piston, extra wide inverted surround radiator
- Subwoofer:
  - 8W7571, 8" (20cm) cono Focal "W" composite sandwich
  - Medie: 6W0452, 6.5" (16.5cm) cono Focal "W" composite sandwich
  - Tweeter: TB872, 1" pure Beryllium inverted dome tweeter
- Costruzione: 0.88"(22mm) and 1.2" (30mm) panels with internal braces
- Finitura: Verniciatura nera dei pannelli inferiore e superiore, corpo nero.
- Dimensioni: 12.8" x 19.6" x 15.6" (320mm x 490mm x 390mm)
- Peso netto: 35 kg