

KME VL8IBK VERSIO 2-WAY PASSIVE BASS REFLEX BLACK

307,30 € tax included

Reference: KMVL8IBK



KME VL8IBK VERSIO 2-WAY PASSIVE BASS
REFLEX BLACK

In this version without handles and flanges the casings are equipped with always 6 M8 treads to adapt wall mounts, u-brackets or eyebolts.

All models are invariably available in black polyurethane coating. Inside work high resilient drivers developed to the latest technologies, which also contribute to a weight reduction due to neodymium magnets.

top unit is equipped with a 1" high-frequency driver.

- Components: 8" + 1" Neodymium
- Dispersion (h x v): 85° x 55° Waveguide (elliptical)
- Nominal load AES / prog. (watts): 250 / 500
- Impedance (Ohm): 8
- SPL (nom. / max.) dB*: 95 / 119
- Frequency range: 75 Hz - 19 kHz
- Connectors: 2 x terminal screw connectors, 2 x Speakon NL 4 Neutrik optional
- Finish: PU coating black
- Special features: 6 M8 treads
- Optional accessories: speaker wall mount (article 2-512-019), U-bracket (article 1-910-043), M8 eyebolts (article 5-350-000), universal mounting plate with TV spigot (article 2-512-007) ,100 Volt transformer
- Protective grille: black comb grid with acoustic foam
- Dimensions (WxHxD) mm: 280 x 460 x 245
- Weight (kg): 9
- Design: top unit / full-range
- Recommended subwoofers: passively channelled: VB 15 t, VB 15 w actively channelled: VB 215, VB 18
- Recommended amplifier: SPA 500 F, SMA 2000