

## KME VLX15 VERSIO X PASSIVE 2-WAY LOUDSPEAKER

**999,00 € tax included**

Reference: KMVLX15



KME VLX15 VERSIO X PASSIVE 2-WAY  
LOUDSPEAKER

The VLX15 is a passive 2-way loudspeaker which is both suitable for speech and music reproduction as a top, fullrange speaker, or stage monitor.

### Multifunctional:

- enclosure design enabling several setup variants (speaker stand, monitor, frontfill)
- compact dimensions and moderate weight due to neodymium speaker
- speaker flange with adjustable angle
- flying ability due to optional flying hardware

### Durable and value stable:

- Wooden casing with weatherproof PU coating
- High quality and high load capacity components
- Impregnated loudspeaker membrane for inside and outside applications

### Sound:

- Smooth and balanced reproduction of the high frequencies
- Low acoustic feedback behaviour
- Natural and transparent sound

### Specifications:

- components: 15" + 1" (1.4" voice coil)
- dispersion: 85° x 55° elliptical
- nominal load AES/program (Watt): 500 / 1000
- impedance (ohms): 8
- SPL nom./max. (dB): 98 / 125
- frequency range (-10dB): 55 Hz – 20 kHz
- connectors: 2x Neutrik Speakon NL4
- finishing: PU coating (black or white)
- protective grills: sturdy front grille with acoustic foam
- special features: 2x M8 mounting thread, 1x M8 safety thread, speaker stand receptacle with adjustable angle, 2x handles
- dimensions W x H x D (mm): 445 x 700 x 425

- weight (kg): 21