

## LD SYSTEMS STINGER 10 G3 DIFFUSORE PASSIVO 2 VIE 1X10" 300W

**34,00 € tax included**

Reference: LDEB102G3



LD SYSTEMS STINGER 10 G3 DIFFUSORE PASSIVO  
2 VIE 1X10" 300W

This highly professional 2-way loudspeaker is designed for absolute, long-term reliability. With its multifunctional bass reflex cabinet as a full range speaker, satellite and ground monitor, it is suited to mobile and fixed PA systems. The Stinger® 10 G3 provides 300 watts of continuous power, the maximum sound pressure level is 120 dB. Its specially developed 10" woofer and the BMS HF driver achieve a powerful bass reproduction and fresh natural highs. The wave guide of the tweeter has been developed using the Boundary Element Method (BEM), a numerical simulation of the sound radiation and dispersion. It reduces reflections from the floor and ceiling and prevents sidelobe levels and thus achieves a controlled and homogeneous dispersion. The Stinger® 10 G3 is designed as a real all-round workhorse. The cabinet is made from robust birch plywood and offers exceptional stability and durability thanks to its extremely durable polyurea coating. The features include a steel grille, a Dual-Tilt stand attachment, flight points and ergonomic handles. The Stinger® 10 G3 is an affordable solution for professional PA applications' extensive accessories support the use on stage and in fixed installations.

- Tipo di prodotto Altoparlante PA
- Tipo Passivo
- Dimensioni woofer 10 "
- Dimensioni woofer 254 mm
- Magnete woofer Ferrite
- Marca woofer Custom Made
- Bobina woofer 2 "
- Bobina woofer 50,8 mm
- Horn BEM corno ottimizzato direttività costante
- Dimensioni driver HF 1 "
- Dimensioni driver HF 25,4 mm
- Magnete driver HF: Ferrite
- Marca driver HF BMS
- Bobina driver HF 1 "
- Bobina driver HF 25,4 mm
- Angolo di dispersione (H x V) 90 ° x 50 °
- Sollecitazione (RMS) 300 W
- Sollecitazione (Peak) 600 W
- Risposta in frequenza 65 - 20000 Hz
- SPL (1 W / 1 m) 96 dB

- SPL massimo 121 dB
- Impedenza 8 Ohm
- Protezioni Driver HF
- Ingressi altoparlante 1
- Connessioni di ingresso dell'altoparlante Speakon compatibile
- Uscite altoparlante 1
- Connessioni di uscita dell'altoparlante Speakon compatibile
- Materiale cassa Compensato 12 mm
- Superficie cassa Poliurea
- Modello cassa Bass reflex
- Angolazione monitor 54 °
- Larghezza 325 mm
- Altezza 527 mm
- Profondità 308 mm
- Peso 11,5 kg