

YAMAHA CL3 DIGITAL MIXER CONSOLE

12.530,00 € tax included

Reference: YAACL3

YAMAHA CL3 DIGITAL MIXER CONSOLE



Una miscela ideale di dimensioni compatte e di capacità di canali per una grande varietà di applicazioni live e installazioni.

Canali di input: 64 mono, 8 stereo.

Configurazione Fader: 16-fader sezione sinistra, 8-fader sezione Centralogic, 2-fader sezione master

Supporto in alluminio per iPad.

Meter bridge opzionale.

Dimensioni:

Larghezza: 839mm (33 1/8in)

Altezza: 299mm (11 3/4in)

Profondità: 667mm (26 1/4in)

Peso: 29kg (63.9lb)

Sampling frequency rate:

Internal: 44.1kHz / 48kHz

External: 44.1kHz: +4.1667%, +0.1%, -0.1%, -4.0% (± 200 ppm), 48kHz: +4.1667%, +0.1%, -0.1%, -4.0% (± 200 ppm)

Signal delay: Less than 2.5ms, OMNI IN to OMNI OUT, Fs=48kHz

Total harmonic distortion: Less than 0.05% 20Hz-20kHz @ +4dBu into 600 Ω , OMNI IN to OMNI OUT, Input Gain = Min.

Frequency response: +0.5, -1.5dB 20Hz-20kHz, refer to +4dBu output @ 1kHz, OMNI IN to OMNI OUT

Dynamic range: 112dB typ.: DA Converter / 108dB typ.: OMNI IN to OMNI OUT, Input Gain = Min.

Crosstalk: -100dB*1, adjacent OMNI IN/OMNI OUT channels, Input Gain = Min.

Power requirements: US/Canada: 120V 60Hz, Japan: 100V 50/60Hz, China: 110-240V 50/60Hz, Korea: 220V 60Hz, Other: 110-240V 50/60Hz

Power consumption: 170W: Internal Power Supply / 200W: Simultaneous use of Internal PSU and External PW800W

Temperature Range: Operating temperature range: 0 - 40?, Storage temperature range: -20 - 60?